

Product Description:

ΣJ Series Sub speaker utilise high power low frequency drivers with structurally solid enclosures. The ΣJ Series Sub speakers deliver extended low frequency bandwidth with excellent punch. Suitable for Performing Arts, Auditoriums, Clubs, Houses of Worship, Entertainment Venues and Indoor Sports Facilities.



Key Features and Benefits:

- High SPL and sensitivity
- 2 x 18" high power low frequency transducer
- 2 x NL4 connectors
- Computer aided design to optimise frequency and phase response
- Multi purpose cabinet design for FOH
- Mounting points for permanent installation (wall, ceiling, under balcony)
- Combine with any ΣJ212 or ΣJ215 Series high power speaker for extended full range frequency, high quality music reproduction
- Powder coated grill
- Durable Polyurethane textured base paint
- 1 x NL4 connector included in packaging

System specification:

Construction	Medium-Density Fiberboard
Transducers	2 x 18" Woofer
Frequency Response (-3dB)	35Hz-1.8kHz
Rated Power	1600W
Sensitivity (1W @ 1m)	102dB
Maximum SPL	134dB/140dB (Peak)
Rated impedance	4Ω
Connector	2x NL4
Dimension (W x H x D)	567mmx 1075 mm x786 mm
Net Weight (1piece/pack)	85kg (187lb)
Gross Weight (1 piece/pack)	90kg (198lb)

