



## Product Description:

Two way phase-reversed full range professional speaker, professional and efficient two transducers, computer simulating design.

## Key Features and Benefits:

- Two transducers two way full range.
- High SPL and sensitivity speaker.
- One 15" big power low frequency transducer.
- One compression driver with 1.75" titanium diaphragm.
- Driven by one amplifier with the possibility to drive a second 8 Ohm monitor.
- (55°-100°) x 50° width direction to get more widely enlarged capability.



## System specification:

System	Built-in Crossover Two Way Full Range Speaker
Cabinet	Plywood covering black toast painting
Drivers Quantity	15" x 1 (Bass) 1 x Ø44mm Driver
Frequency Response (-3dB)	50Hz - 18kHz
Frequency Response (-10dB)	45Hz - 20kHz
Sensitivity (dB/1M/1W)	95 dB
Impedance	8Ω
Recommendatory Power (RMS/W)	250 W
Max Sound Level (dB/1M)	120 dB
Tweeter Dispersion (HxV)	(55° - 100°) x 50°
Harmonic Distortion	≤ 1%
Connectors	2xNL4, 1+/1-
Dimensions (WxDxH)	430mm x 429mm x 621mm
Packing Dimensions (WxDxH)	712mm x 517mm x 541mm
Net Weight (Kg/pcs)	18 kg
Gross Weight (Kg/pcs)	20 kg