



Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement and stage monitoring in Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The MU Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- 2 x 15" high power low frequency transducer with 100mm voice coil
- 2 x NL4 connectors
- Passive configuration
- RMS 1200W
- Computer aided design to optimise frequency and phase response
- · Cabinet designed for FOH use
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency, high quality music reproduction
- · Powder coated grill with foam backing
- Durable Polyurethane textured base paint



System specification:

Construction	15mm Birch Plywood
Transducers	1 x 3" HF Compression Driver + 2x15" LF
Frequency Response (-3dB)	46Hz-17kHz
Rated Power	1200W (RMS)
Sensitivity (1W @ 1m)	98dB
Maximum SPL	127dB/133dB (Peak)
Rated Impedance	4Ω
Connector	2 x NL4
Dimensions (W x D x H)	530mm (20.9") x 530mm (20.9") x 1075mm (42.3")
Packaging Dimensions (1 piece/pack)	660mm (26") x 660mm (26") x 1195mm (47")
Net Weight (1 piece/pack)	60kg
Gross Weight (1 piece/pack)	67kg