

## Product Description:

Beta Three<sup>®</sup> B Series professional amplifiers is a new design high-performance power amplifier with low distortion high damping factor and smooth sound.



## Key Features and Benefits:

- Rear panel selection switch for Stereo, Parallel and Bridged modes, including
- Low-Cut filter, Ground lift and Limiter switches
- Operates within 8Ω and 4Ω loads
- Innovative heatsink with front to back air flow for efficient cooling
- Variable fan speed is automatically adjusted by temperature
- Electronically balanced XLR inputs
- Touch proof binding post and Speakon outputs
- Precision indented level controls, power switch
- Protect, Peak and Signal LEDs indicators for each channel
- Amplifier protection includes short circuit, excessive temperature and DC on outputs

## System specification:

|                     |                         |
|---------------------|-------------------------|
| Rated Power (8Ω)    | 1500Wx4                 |
| Rated Power (4Ω)    | 2500Wx4                 |
| Frequency Response  | 20Hz - 20kHz(+/- .25dB) |
| Type                | Class D                 |
| Peak Output Voltage | 200v                    |
| Damping factor      | >500:1(100Hz)           |
| THD                 | <0.25%                  |
| Input Interference: | XLR Shocket             |
| Power Required      | 220-230V, 50/60 Hz      |
| Dimension           | 485mmx482mmx88mm        |
| Net Weight          | 25kg                    |