Product Description:

Portable and installed loudspeakers used in applications including soundreinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc.It Can be used as Stage Monitor as well.

Key Features and Benefits:

- Two transducers two way full range
- · High SPL and sensitivity speaker
- One 15" big power low frequency transducer
- One compression driver with 0.44 mm titanium diaphragm
- Drived by one amplifier 90° x 60° width direction to get more widely enlarge capability
- With computer optimize simulated design to get better frequency and phrase features
- Multiple flexible installation methods
- Suitable for full sound field enlarge, club and dancery etc public using
- Suitable for any big sound engineering project or enlarge, returning listen, repair listen of fluxion performance system
- · Used for high quality output replaying music
- Can be assorted with ΣΒ115H, ΣΒ118D, ΣΒ218 high capacity bass box



System specification:

System	LF: 15" x 1, HF: 44mm x 1
Frequency Response(-3db/-10dB)	50Hz-20kHz/40Hz-20kHz
Rated Power	300W
Sensitivity (1W/1m)	97dB
Average/Maximum SPL	122dB/128dB
Crossover Frequency	2.3kHz
Dispersion (HxV)	90° x 60°
THD	<3%
Rated Impedance	8Ω
DC Impedance	5.8Ω
Connectors	NL4 x 2
HF Protection	Electronical Protect
Dimension (WxHxD)	490mm × 390mm × 680mm
Packaging Dimensions (W x H x D)	588mm × 480mm × 775mm
Net Weight	30kg
Gross Weight	33kg