

Portable and installed active loudspeakers used in applications including soundreinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc

## **Key Features and Benefits:**

- Three transducers two way full range
- · High SPL and sensitivity speaker
- Two 15" big power low frequency transducer
- One compression driver with 0.44 mm titanium diaphragm
- Drived by one amplifier 90° x 40° width direction to get more widely enlarge capability
- With computer optimize simulated design to get better frequency and phrase features
- Multiple flexible installation methods
- Suitable for full sound field enlarge, club and dancery etc public using
- Suitable for any big sound engineering project or enlarge, returning listen, repair listen of fluxion performance system
- Used for high quality output replaying music
- Can be assorted with ΣΒ115H, ΣΒ118D, ΣΒ218 high capacity bass box



## **System specification:**

System	Bass: 15" x 2, Treb: Φ44mm x 1
Frequency Response(-3db/-10dB)	50Hz-16kHz/45Hz-18kHz
Rated Power	600W
Sensitivity (1W/1m)	97dB
Average/Maximum SPL	128dB/134dB
Crossover Frequency	2kHz
Dispersion (HxV)	90° x 40°
THD	<3%
Rated Impedance	4Ω
DC Impedance	3.6Ω
Connectors	NL4 x 2
HF Protection	Electronical Protect
Dimension (WxHxD)	540mm × 503mm × 1074mm
Packaging Dimensions (W x H x D)	1165mm × 630mm × 608mm
Net Weight	52kg
Gross Weight	57kg