



BS5002T

PUBLIC ADDRESS SERIES | Versatile Full-Range Plastic Speaker

Product Description:

β³ BS5002T is a two-way full range bass reflex speaker box comprised of 5.25" LF unit and 0.5" PEL tweeter. A switchable transformer built at the back allows for 7W/15W/30W/8Ω working mode. With an optional U bracket, the compact and exquisite design is smartly used for public address in meeting rooms, schools, office buildings, where high quality sound reinforcement is needed for small and medium venues.



Key Features and Benefits:

- Full range of plastic speaker
- One 5.25" (133mm) Woofer
- One 0.5" (12.8mm) Tweeter
- Built in Transformer
- Power tapping at 7W/15W/30W/8Ω
- Mounting bracket available

System specification:

System	Two-way full range speaker system
System components	1x5.25" LF, 1x0.5" PEI tweeter
Frequency Response (-3dB)	60Hz-20kHz
Frequency Response (-10dB)	55Hz-20kHz
Sensitivity (1W@1m)	86dB
Max. SPL (1m)	106dB/112dB (Peak)
Power (70V,100V Tappings)	7W, 15W, 20W
Power (Bypass/Continuous, Program)	50W, 100W
Dispersion (HxV)	150°x150°
Impedance (Bypass)	8 Ohms
Cabinet	Plastic
Installation	Optional Bracket
Painting	Enclosure and Grill with Black Painted
Connector	Block Terminal
Cabinet Dimensions (W x D x H)	146.5mm x 146mm x 230mm
Package Dimension (W x D x H)	385mm x 220mm x 315mm
Net Weight (Piece)	2.6kg
Gross Weight (Pair)	6.6kg